# Comment Letter O9

# Hingtgen, Robert J

Donna Tisdale <tisdale.donna@gmail.com>

Saturday, March 01, 2014 1:02 PM

Hingtgen, Robert J; Fogg, Mindy, Gungle, Ashley, Wilson, Adam

Subject **Attachments** 

Solec DPEIR-CPV brochure says no grading Solec brochure\_cpv\_en.pdf; Solec CX-S530-II\_Technical\_Data\_Sheet.pdf; Solec plug-and-

sun\_en.pdf; Soitec CPV Installations\_V10.0 Feb 2014.pdf

Comments on Soitec Solar Development Draft Program Environmental Impact Report (DPEIR): 3800 12-010; Tierra Del Sol, 3300 12-010 (MUP), 3600 12-005 (REZ), 3921 77-046-01 (AP); Rugged Solar, 3300 12-007 (MUP): Environmental LOG NO.; 3910 120005(ER) & Request of re-circulation of a revised DEIR

Hello Robert.

Please take note of and include the following information in the record for Soitec's Boulevard projects DPEIR and MUPs. I am submitting them as an individual and on behalf of the non-profit group Backcountry Against

The attached Soitee CPV brochure is posted on their website and makes the following apparently false claims: http://www.soitec.com/pdf/brochure\_cpv\_en.pdf

- Few site requirements
- (no grading or water required)
- No water needed for operation or cooling
- Minimal impact on vegetation and wildlife
- Dual use with agriculture possible.

These claims are demonstrated as false when based on their estimated grading and water use and other significant impacts for Rugged Solar, Tierra Del Sol Solar, LanWest and LanEast, removal of agriculture preserve, and through other information included in the DPEIR, and as demonstrated by Soitec's other projects.

The false claims, regarding no grading and minimal impact on vegetation and wildlife, are also contradicted by Soitec's own public relations Fact Sheets, and other documents, with evidence of clear grading, removal of virtually all vegetation, and disturbance of natural soil / binders at their following existing sites:

- 1. Soitec's 1.37MW Questa New Mexico facility Fact Sheet (173 Concentrix 18' x 21' CPV dual trackers): claims of zero water gallons per year for power production http://www.soitec.com/pdf/sites/Soitec\_Questa\_factsheet\_en.pdf
- 2. Soitec's 1.68 MW Newberry Solar 1 site in Newberry Springs, CA (60 CX-S530 CPV systems) Newberry Springs ID Card: http://www.soitec.com/pdf/sites/Soitec Newberry ID card.pdf
- 3. Soitee's Newberry Springs PR video (see video starting at 2:31 minutes for evidence of clear grading at Newberry site and at 3:30 where the video fades out just as the main glare from the CPV panels would show up): http://www.soitec.com/videos/soitec-newberry-springs/
- 4. Soitec's Hazelemer 500kV site Durban South Africa Fact Sheet (32 CX-S42 systems): http://www.soitec.com/pdf/sites/Soitec\_Hazelmere\_factsheet\_en.pdf
- 5. Soitec's Wadi El Natrun Egypt 40kW Fact Sheet (5 Soitec CX-P6 systems) http://www.soitec.com/pdf/sites/Soitec Wadi El Natrun factsheet en.pdf
- 6. Soitec's Touwsrivier Western Cape South Africa 82kW (demonstration project) Fact Sheet (Soitec CX-P6): http://www.soitec.com/pdf/sites/Soitec Touwsrivier factsheet en.pdf

# **Response to Comment Letter O9**

# **Backcountry Against Dumps Donna Tisdale** March 1, 2014

- 09-1This comment is introductory in nature and does not raise an environmental issue for which a response is required.
  - The commenter asserts that a brochure located on the Project applicants' website makes false claims about the applicants' concentrator photovoltaic (CPV) technology, and points to other parts of the applicants' website to support the assertion. Neither the applicants' brochure nor the other citations to the applicants' website raise environmental issues concerning the DPEIR. The DPEIR analyzes the Proposed Project and site-specific impacts related to grading, vegetation and wildlife, use of soil binders, agriculture, glare, and water use for construction and Any statements made in general operations. publications of the applicants, or in publications related to other projects, are not relevant to the Proposed Projects or the project and site-specific analysis conducted in the DPEIR. The comment does not demonstrate how general information published on the Project's technology undermines the County's evaluation of the Proposed Project. Accordingly, no further response can be provided. However, the comment is acknowledged and will be included in the

October 2015 7345 Final PEIR

09-2

O9-1

09-2

**O9-3** 7. Soitec's 680kW Puertollano, Castilla-La Mancha, Spain CPV plant Fact Sheet (Soitec CX-P6): http://www.soitec.com/pdf/sites/Soitec Puertollano factsheet en.pdf 8. Soitec's 630kW Rains, Var , France Fact Sheet (80 32m2 CPV Systems): http://www.soitec.com/pdf/sites/Soitec Rians factsheet en.pdf 09-2 9. These and other projects are documented in the Soitec CPV Installation document dated February Cont. 2014, where all but 2 of the 12 projects shown are clear graded: http://www.soitec.com/pdf/Soitec CPV Installations V10.0.pdf Please also include these Soitec documents into the record Soitec's February 2014 CPV technical data sheet that is attached and also posted here: http://www.soitec.com/pdf/CX-S530-II Technical Data Sheet.pdf 09-3 · Soitec's 3.4kW Plug & Sun off-grid tracker system with 24/7 battery backup that can be used as alternative distributed on-site generation: http://www.soitec.com/pdf/plug-and-sun\_en.pdf Regards, Donna Tisdale 619-766-4170 PO Box 1275 Boulevard, CA 91905 bcc: interested parties

Final Program Environmental Impact Report (FPEIR) for review and consideration by the decision makers.

The comment letter and attachments will be included in the FPEIR for review and consideration by the decision makers as requested by the commenter. Related to the use of distributed generation as an alternative, please refer to the response to comment O10-102 and ALT2.

# The product

Soitec is a leading manufacturer and supplier of concentrator photovoltaic (CPV) systems using highly efficient Concentrix technology based on German engineering excellence. The company has a track record, with the first commercial power plants installed in 2008. We offer innovative CPV systems and additional services related to the project development, as well as supporting services for financing and operation & maintenance.

# Why Soitec CPV power plants?

Soitec power plants are a profitable and ecological investment at the same time. Using Concentrix technology, Soitec offers a reliable, proven, costeffective and bankable solution for energy generation in the sunniest regions of the world.

Concentric technology afters low cost of energy combining

- · Low-cost materials
- . High module efficiencies
- · High energy yield production

Highest efficiencies and hest performance of all solar technologies - especially at hot ambient

- · Tracking enables constant power output curve throughout the day
- · Solar production matches peak load.
- . Only one third of the energy loss due to heat compared to conventional silicon PV modules

# Local value:

Soiter power plants can be easily and flexibly installed using local content and


- · Few site requirements
- (no grading or water required) · Installation with local workforce and only a few specialists
- · Commissioning in phases
- . Sustainability of technology eases the permitting

Soites power plants use the most environmentally friendly solar

- Short energy payback time
- . Low environmental footprint
- No need for water during operation or for cooling
- · Optimum use of land

The reliability of our power plants is proven by field data and through extensive reliability testing (IEC62108, CEC listing). This is achieved by a simple, robust and conservative design and material approach that is well suited for mass production:

- · Glass-glass design, comparable to a double-glazing window with 30-40 years lifetime
- · Small lens aperture area to reduce power consumption and working temperature of the cell
- · Manufactured with full automation, proven materials, well-known processes and standard use equipment.



October 2015 7345

# The technology

# How it works

Concentrix technology uses Fresnel leases made of silcone-on-glass to concentrate sunlight by a factor of 500 onto tiny, highly efficient, multi-junction solar cells. These cells are mounted on a base plate made of glass and convert the concentrated light directly into

electrical energy. The lens plate and the base plate are connected via a metal frame and comprise a concentrator module.

The concentrator modules are mounted on a two-axis tracking system that follows the sun, it ensures that the focus point of the concentrated sunlight is directly on the cells at every moment of the day.



# Components of Concentrix technology

Soitec's Concentrix technology is a very innovative, high-performance technology that consists of well-adapted, high-quality components. The components are designed for longevity and durability to ensure high performance during the lifetime of the systems.

#### Multi-junction cells

Concentrix technology uses optimized III-V based multi-junction cells (GainP/GainAs/Ge).

For almost 20 years, multi-junction cells have been used in space applications. The energy yield and the potential of these high-efficiency cells are enormous, in the lab, efficiencies of more than 41% have been achieved. This is double the efficiency of conventional solar cells.

In comparison to conventional solar cells, multi-junction cells are more efficient but also more exponsive to manifacture. By using cost-effective concentrating lenses to focus the surlight on these multi-junction cells, it is possible to minimize the amount of semiconductor material. The cells Soltec uses are only millimeters in diameter. This principle crabiles the manufacturing of CPV modules that are highly efficient and inexpensive at the same time.

#### **CPV** module

Soitec's Concentrix modules are made up of a lens plate (Fresnel lens) and a base plate on which high-performance solar cells are mounted.

For its module construction, Solitec uses elements from the circuit board industry and an insulating glass technology that are both cost-effective and have been proven reliable over many years. Procision and quality in the module manufacturing lead to an extremely high everage module efficiency of almost 30%. Solitec's Concentrix modules are IEC62108 certified and won listing with the California Energy Commission (ICEC).

#### Inverte

Soited selects the most reliable and efficient inverters, enabling electricity conversion with very low losses. Two different types of inverters exist: string inverters and central inverters. Concentrix

technology has been developed so that it can use both types of inventors.

# Tracking system

Concentrix technology from Solter requires the use of a two-axis tracking system. This system ensures that the focus point of the concentrated sunlight is exactly on the cells at every moment of the day. It uses unique, proprietary software and algorithms to position the tracker. Besides the astronomical positioning, it monitors the DC power output and calculates the next optimum position to maximize the system's power generation. Soltec uses the most reliable tracking systems, enabling constant energy production even at high wind speeds and requiring only simple maintenance for gases and motors.



# The company

Sollec is an international company, a world leader in generating and manufacturing revolutionary semiconductor materials at the frontier of the most exciting challenges for energy and electronics.

Soitec's products and technologies dramatically improve energy-efficiency, performance, miniaturization, reliability and the quality of our daily life.

Headquartered in Bernin, France, with two high-volume fabs on-site, Solec has offices and fabs in the United States, Germany, Japan, China, Taiwan and Singapore, Solec shares have been listed on Europed Paris since 1999.

In the solar market, Soitec is one of the leading technology providers of CPV modules and systems based on its. Concentrix technology. Soitec has a proven track record

with the first commercial power plants installed in 2008 and world-leading module efficiencies of almost 30%. Concernix technology is a result of more than 15 years of research and 6 years of industrial implementation. It is IEC certified and CEC listed as well as field proven.

Soite: operates one of the world's most modern production lines for manufacturing CPV modules. Reliable, fully automated manufacturing processes ensure the high quality and durability of Soitec's products.

# Soitec's Concentrial technology originated at the Fraunhofer Institute for Solar Energy Systems ISE, the largest solar research into the technology was conducted over more than 10 years. In 2005, Fraunhofer ISE spun off a company to commercialian the technology, it developed a complete CPV system requipped with modules, a tracking system and an inverter. The company was acquired by Soitec in 2009.

# Optimizing CPV technology


With our R&D department, we are consmually working on improvements in the product design, the production quality and the output of our Concentrix technology in order to increase efficiency, to lower costs even further and to guarantee the product quality and performance for our customers.

By combining proven and certified Concentrix, technology with Soiteck Smart Cut\* and Smart Stacking\* technologies, Soitec is paving the way for market-leading solar power plant efficiencies of 35%.

# Leading the solar energy revolution in high-DNI regions . More stable production profile Higher revenue generated Easier grid management . Constant power production throughout the day including peak times when it is most valuable Very high electricity yields through low heat degradation at hot ambient temperatures Local content, local value, local jobs · Local jobs for construction, operation and Economic development through local manufacturing of components · Indirect jobs for the local economy Clean energy with a light environmental footprint No water needed for operation or cooling Minimal impact on vegetation and wildlife . Dual use with agriculture possible · Short energy payback time · High recyclability low cost of energy Lowest cost per kWh . Twice as efficient as state-of-the-art PV · Low-cost materials such as glass and silicone Semiconductor area reduced to a fraction of the solar module size.

October 2015

7345





# Soitec Concentrix™ Technology Powers CPV Solar Power Plant in New Mexico

Soitec is a world leader in developing and manufacturing revolutionary semiconductor materials for microelectronics and energy applications. With the commercialization of its proprietary utility-scale Concentrix" concentrating photovoltaic (CPV) technology, the company is now bringing its formidable R&D and manufacturing expertise to the solar power industry. Concentrix" CPV systems have amongst the lowest environmental impact and shortest energy payback of any solar power technologies.

# The Project

The CPV power plant is located in one of the smallest villages in the country. Stuated on remediated land on a mine tailings facility near Questa, New Mexico, the Cheron solar power plant employs Soltects Concentris, "technology which includes 173 solar tracking systems approximately 18" by 21" in size. Each system houses Fresnel Jenses that concentrate sunlight 500 times onto small, high-efficiency multi-junction solar cells. For maximum performance, the systems are mounted on pivoting dual-axis trackers that follow the sun's movement throughout the day. The tracking systems maximize energy generation, providing it to the local electric utility when it is needed most. The plant is capable of producing 1.37 MW, of clean, renewable energy - enough to power all of Questa's 350 homes.



www.soitec.com



With its high altitude of 7,500 feet - and preponderance of clear skies and direct sunlight - the mountainous New Mexico region provides an ideal's solar resource for CPV systems. The Questa mine tailings site required a solar power technology that could adapt to the remediated lands unique environmental needs. Soitoc delivered a CPV solution with maximum energy-generating capacity and minimal impact on the local natural environment. Additionally, construction and on-going operations and maintenance efforts at the solar power plant provide much-needed economic development and job divensification for the Guesta community.

#### The Benefits

Soltec's Concentrix." CPV technology has many industry-leading benefits including amongst having the shortest energy payback of any solar power technology, as well as an exceedingly low environmental footprint. The systems have a high content of recyclable material, and require no water for ongoing operations - a major advantage in the hot, dry desert climates - most amenable to solar energy production.

Additionally, since Soitec's CPV systems are pedestal-mounted, they are slopetolerant and require no disruptive land grading. The pedestal foundations reduce the impact on native vegetation and allow for dual land use. Finally, their shallow foundation design provides site flexibility and requires minimal ground penetration, making utility-scale solar power installations even more cost effective.

The Questa solar power plant confirms the attractiveness of Soitec's renewable energy technology – which generates large amounts of power with industry-leading efficiency and low environmental impact – in areas such as New Maxico that have abundant surshine.

#### About Soitec

Soltec is an international manufacturing company. a world leader in generating and manufacturing revolutionary semiconductor materials at the frontier of the most exciting energy and electronic challenges. Soitec's products include substrates for microelectronics (most notably SOI: Silicon-on-Insulator) and concentrator photovoltaic systems (CPV). The company's core technologies are Smart Cut", Smart Stacking", and Concentrix", as well as expertise in epitaxy. Applications include consumer and mobile electronics, microelectronicsdriven IT, telecommunications, automotive electronics, lighting products, and solar power plants for large-scale utilities. Soitec has manufacturing plants and R&D centers in France, Singapore, Germany, and the United States.

For more information, visit the website www.soitec.com

# **Project Highlights**

Location	Questa, New Mexico (USA)
Power Plant Commissioned	January 2011
Power Plant Capacity	1.37 MW <sub>o</sub> installed capacity
Number of CPV Systems	173
Water Used	Zero gallons per year in power production

Softec ... 16550 Via Espello San Diego, CA 92127 (USA) T. +1 858 746 9000 sales soler@softec.com





# **INFO & CONTACTS**

#### Soitec Solar 16550 Via Esprillo San Diego, CA 92127 (USA) T. +1 858 746 900

# Contact

sales-solar@soitec.com

#### Website

www.soitec.com


# ABOUT SOITEC

Solise is a world leader in generating and manufacturing revolutionary semiconductor materials, at the frontier of the most exciting energy and electronic challenges. The company has been founded in 1992 and is stock listed at the Euronext in France.

Soitec Solar is an industrial Concentrator Photovoltaic (CPV) Systems manufacturer. The company has a track record in more than twenty countries. Our innovative CPV systems are specifically designed for the sunniest regions of the world.

We also offer a strong expertise in project development as well as operation and maintenance services. By exploiting the synergies of our proprietary semiconductor technologies for solar, we are committed to bring solar cells with record efficiency into production to further increase our systems efficiency.

# **CPV TECHNOLOGY**



Solite's Concentrix" technology uses Fresnel lenses made of sisione-on-glass to concentrate sunlight by a factor of 500 ceto fine, highly-efficient multi-junction solar cells on the receiver plates. The cells convert the light directly to electrical energy. Lens plates and receiver plates are connected with a metal frame and comprise a CPV Module.

The CPV Modules are mounted on a dual-axis tracker that follows the sun. It ensures that the focus point of the concentrated sunlight is on the cells at every moment of the day to maximize the power output.

6.3014 Soles S.A. I Constrain "and Soles" are trademarks of Soles S.A. I Vestion Habrury 2014. I Design VHCK com-



# Concentrator Photovoltaic Power Plant in Hazelmere

This CPV Power Plant was installed to power the COP17 Climate Conference in Durban, November 28 – December 9, 2011. It is the first commercial CPV Power Plant in South Africa, inaugurated by His Excellency, President Jacob Zuma in December 2011.

Soitec is a leading manufacturer and supplier of Concentrator Photovoltaic (CPV) Systems using highly efficient Concentrix" technology based on German engineering excellence. The company has a successful track record, with the first commercial power plants installed in 2008. We offer innovative CPV Systems and additional services related to project development, as well as supporting services for financing, operation and maintenance.

Location	Hazelmere, Verulam, ERF 1970
Soitec involvement	Turnkey contract
Capacity	S00 kW <sub>p</sub> (32 Systems)
CPV System type	Soitec CX-S420
Construction	October - November 2011
Grid connection	December 2011




www.soitec.com



# Utility-Scale Power Plants Based on Concentrix™ Technology

# Concentrator Photovoltaic Power Plants for high irradiation regions

- Highest efficiency, best performance
- · Local value, local content, local jobs
- · Lowest cost of electricity
- · Most environmentally friendly solar technology



www.soitec.com



English version

# Concentrator Photovoltaic Power Plant in Wadi El Natrun



In the frame of the NACIR Project, the most advanced European Concentrating Photovoltaic (CPV) technologies have been installed in Egypt. NACIR is a European initiative dedicated to cooperation with mediterranean partner countries in the field of concentrating photovoltaic. Soitec installed a 40kW<sub>p</sub> stand alone CPV Power Plant used for water pumping and irrigation purposes. This collaborative project focused on EU cooperation with mediterranean partner countries.

This demonstration project illustrates the use of the Soitec CPV Concentrix\*\* technology in an island system: a storage solution feeds an irrigation water pump and a desalination factory. The CPV Systems are integrated in an installation comprising batteries, irrigation pumps and desalination. The control of the electricity consumption is supervised by Fraunhofer ISE.

Location	Wadi El Natrun, Egypt
Customer	National Water Research Center
Installed Systems	5 Soitec CX-P6 Systems
Capacity	40kW <sub>p</sub>
Installation	2010



www.soitec.com

October 2015



# Concentrator Photovoltaic Power Plant in Touwsrivier

Situated at the Aquila Private Game Reserve, Touwsrivier, South Africa, this CPV installation is used as a demonstration for the larger 44 MW<sub>p</sub> solar power plant that will be located on an adjacent site. In addition to supplying energy to the reserve during daylight hours and promoting ecotourism, it serves as a test bed and training ground for the development and construction of the larger site. The CPV Power Plant is owned and operated by Soitec.

Soitec is a leading manufacturer and supplier of Concentrator Photovoltaic (CPV) Systems, using highly efficient and innovative Concentrix" technology. We offer innovative CPV Systems and supporting services, including project development, as well as financing, operation and maintenance. Soitec has a successful track record with the first commercial CPV Power Plants installed in 2008.

Touwsrivier, Western Cape, South Africa
Turnkey contract
Soitec
82kW, (60 kW AC)
Soitec CX-P6
2010




www.soitec.com



# Utility-Scale Power Plants Based on Concentrix Technology

# Concentrator Photovoltaic Power Plants for high irradiation regions

- · Highest efficiency, best performance
- · Local value, local content, local jobs
- · Lowest cost of electricity
- · Most environmentally friendly solar technology



www.soitec.com



# Concentrator Photovoltaic Power Plant in Puertollano

Puertollano, Castilla-La Mancha is a 680 kW<sub>o</sub> CPV Power Plant, part of a 3MW CPV project and one of the first large-scale solar power plants in Europe to use highly efficient III-V multi-junction solar cells. In its four years of operation, data from Soitec's CPV Systems has been closely monitored by ISFOC (Instituto de Sistemas Fotovoltaicos de Concentración CPV) and demonstrated the high availability and efficient energy production levels of Concentrix" technology.

Soltec is a leading manufacturer and supplier of Concentrator Photovoltaic (CPV) Systems, using highly efficient and innovative Concentrix" technology. We offer innovative CPV Systems and supporting services, including project development, as well as financing, operation and maintenance. Soitec has a successful track record with the first commercial CPV Power Plants installed in 2008.

Location	Puertollano, Castilla-La Mancha, Spain
Soitec involvement	Turnkey contract
Customer	ISFOC S.A.U.
Capacity	680 kW <sub>p</sub>
CPV System type	Soitec CX-P6
Installation	2008






# Utility-Scale Power Plants Based on Concentrix Technology

# Concentrator Photovoltaic Power Plants for high irradiation regions

- · Highest efficiency, best performance
- Local value, local content, local jobs
- · Lowest cost of electricity
- Most environmentally friendly solar technology



Soitec

English version

# Concentrator photovoltaic power plant in Rians

# The power plant


This Concentrating Photovoltaic (CPV) power plant in Rians in the French Provence region is the biggest CPV plant in France in 2011. Based on Soitec's Concentrix" technology, the plant consists of eighty 32m<sup>2</sup> CPV systems producing a total of 630kW<sub>p</sub>. This technology is the most efficient in hot and sunny regions. The plant provides enough power for 300 households.

Location	Rians, Var (France)	
Customer	Soitec Solar GmbH	
Contract type	Turn key project	
Installed systems	80 Soitec CX-P6 systems	
Capacity	630kW <sub>p</sub> *	
Site area	1.8 hectare	
Grid connection	June 2011	
Annual energy yield	1000MWh/year	
Number of households	300	

<sup>\*</sup>Wint-peak, Standard Test Condition: (DNI = 1000W/m², AM1.5D, T<sub>cat</sub> = 25°C



www.soitec.com



# A WORLDWIDE TRACK RECORD

**8**YEARS

of field experience with the first demo installed in 2005

**5**YEARS


of commercial CPV Power Plants, with the first installed in 2008

+20 COUNTRIES

where Soitec CPV Systems and Plug&Sun™ are installed Soitec is an industrial Concentrator Photovoltaic (CPV) Systems manufacturer with more than 41 MW<sub>P</sub> installed. The track record of Soitec's Concentrix<sup>™</sup> technology goes back to 2005, when the first demo CPV System was installed in Germany.


In September 2013 Soitec celebrated the 5th anniversary of its first commercial CPV Power Plant in Spain. Today CPV installations in more than 20 countries demonstrate the competitiveness of Soitec's products. The Concentrix technology is roady for and has indeed begun utility-scale deployment. The most recent installation is a 2.74 MW<sub>p</sub> CPV Power Plant in Hami, China. This installation is the first part of a 20 MW<sub>p</sub> project. We are also looking forward to complete our utility-scale CPV project in Touwsrivier, South Africa, where 850 CPV Systems have already been installed.

# CUMULATED CAPACITY INSTALLED IN MW,



© 2014 Soller; S.A. | Seller Energy | Soller: CPV installations

2




# LIST OF THE SOITEC CPV INSTALLATIONS

COUNTRY SITE		YEAR	SIZE	
Spain	Puertollano, Casaquemada	2006	0.81 MW <sub>p</sub>	
Egypt	Wadi El Natrun	2010	0.03 MW <sub>p</sub>	
Oman	Muscat	2010	0.01 MW <sub>p</sub>	
Jordan	Shams Ma'an	2010	0.01 MW,	
South Africa	Touwarivier	2010	0.08 MW <sub>p</sub>	
USA	Questa	2010	1.37 MW <sub>9</sub>	
France	Rians, Thémis	2011	0.84 MW <sub>p</sub>	
South Africa	Hazelmore	2011	0.48 MW,	
Italy	Santa Lucia, Cerignola and 6 sites	2012	6.11 MW,	
Saudi Arabia	Medinah	2012	0.01 MW <sub>p</sub>	
Tunisia	Om Somaa	2012	0.02 MW <sub>a</sub>	
Chile	Atacama Desert	2012	0.06 MW <sub>e</sub>	
italy	Saletti and 2 sites	2013	2.55 MW,	
Kuwait	Kuwait City	2013	0.03 MW <sub>p</sub>	
USA	Newberry Springs	2013	1.68 MW <sub>a</sub>	
Namibia	Rehoboth	2013	0.03 MW <sub>p</sub>	
China	Hami	2013	2.74 MW,	
South Africa	Touwsrivier	2013	23.8 MW,	
Additional sites in various co	untries	2005-2013	0.49 MW <sub>2</sub>	

TOTAL 41.14 MW<sub>p</sub>

© 2014 Soles S.A. | Solar Energy | Soles CPV installations





QUESTA New Mexico, USA - 1.37 MW,

Installed 2010 173 CX-P6 CPV Systems

SITUATED ON REMEDIATED LAND The CPV Power Plant owned by Chevron Technology Ventures LLC turns mine tallings into a field for solar energy production.



SANTA LUCIA

Installed 2012

74 CX-\$420 CPV Systems

FIRST MW-PROJECT IN ITALY Santa Lucia was the first CPV Power Plant of that size in Italy and paved the way for more CPV projects to



# **CERIGNOLA**

Italy - 1.17 MW.

Installed 2012 74 CX-5420 CPV Systems

STRONG TRACK RECORD IN ITALY Cerignola is one of 7 Italian CPV Power Plants which use Soitec CX-5420 Systems. All are in the range of 0.5 - 1.17 MW.



#### SALETTI Italy - 1.16 MW,

Installed 2013 83 CPV Systems

TRACKERS DEVELOPED IN ITALY Saletti is one of 4 CPV Power Plants in Italy which combine Soltec CX-M500 Modules with locally developed trackers by Alitec.



#### **PUERTOLLANO** Spain - 0.67 MW.

Installed 2008

74 CX-P6 CPV Systems

5 YEARS OF HIGH PERFORMANCE Puertollano is one of the first CPV Power Plants of Soitec's track record. It delivered over 5 years of performance data.



#### RIANS France - 0.63 MW,

installed 2011

80 CX-P6 CPV Systems

CPV IN THE SUNNY PROVENCE By the time of installation the CPV Power Plant in the beautiful Provence region was the largest in France.



#### ATACAMA DESERT Chille - 0.06 MW.

Installed 2012

4 CX-S420 CPV Systems

POWERING MINING OPERATIONS Minera El Tesoro Mining Group and Soitec built up these CPV Systems to power a mining operation in the Atacama Desert.



#### WADI EL NATRUN Egypt - 0.03 MW,

Installed 2010

5 CX-P6 CPV Systems

OFF-GRID POWER FOR IRRIGATION in the course of the European initiative NACIR, Soltec installed an off-grid CPV Power Plant used for irrigation purposes.



#### MEDINAH


Saudi Arabia - 0.01 MW.

Installed 2012 1 CX-P6 CPV Systems


CPV KNOW-HOW TRANSFER


The CPV System at the Medinah College of Technology supports CPV know-how transfer to young Saudi Arabian trainees.

© 2014 Soles: S.A. | Soler Energy | Soles: CPV installations



October 2015





October 2015

Table of Contents

# Table of Contents

1	Definitions
	1.1 Document Version History
	1.2 Document Conventions
	1.3 Abbreviations
2	CPV System Description
	2.1 CX-M500 CPV Module Description
	2.2 CX-T030-II Tracker Description
	2.3 OX-TC2 Tracker Control Unit Description
	2.4 CX-AD1 and CX-AD2 Air Drying Unit Description
3	CX-S530-II CPV System Technical Data
4	CX-M500 CPV Module Technical Data
5	CX-T030-II Tracker Technical Data
6	CX-TC2 Tracker Control Unit Technical Data
7	CX-AD1 Air Drying Unit Technical Data
	CY-AD2 Air Doving Unit Technical Data

© Soitec | CX-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29

Page 2

# 1 Definitions

# 1 Definitions

# 1.1 Document Version History

Version	Date	Changes	In chapter
v50	2013-10-16	Component descriptions added	2
		Technical data update	3 - 8
v51	2013-10-23	CX-AD2 technical data update	8
		CX-M500 "IEC and UL certified" added	2.1
v52	2014-01-29	Technical data CX-T030-II_RoW and _US updated	5

# 1.2 Document Conventions

All units of measurement in this publication are originally metric units. Imperial units are derived from these metric units and are rounded.

The "." is used as a decimal point.

Technical data is subject to change. Images might differ from actual design.

# 1.3 Abbreviations

Abbreviation	Meaning	
AC	Alternating Current	
AM	Air Mass	
CE	European Commission - Declaration of Conformity	
CEC	California Energy Commission	
CPV	Concentrator Photovoltaic	
csoc	Concentrator Standard Operating Conditions: 900 W/m <sup>2</sup> DNI, 20 °C ambient temperature, AM 1.5D spectrum, 2 m/s wind speed.	
CSTC	Concentrator Standard Test Conditions: 1000 W/m <sup>2</sup> DNI, 25°C cell temperature, AM1.5D spectrum.	
DC	Direct Current	
DNI	Direct Normal Irradiation	
IEC	International Electrotechnical Commission	
IP	Ingress Protection	
SC	Short Circuit	
NEMA	National Electrical Manufacturers Association (USA)	
MPP	Maximum Power Point	
RoW	Rest of World	
UL	Underwriters Laboratories	
oc	Open Circuit	
SCADA	Supervisory Control And Data Acquisition	

Page 3 CO-Public CV-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 (© Soitec

# 2 CPV System Description



Fig. 2-1 Main components of the CPV System

The CPV System consists of the main components:

- O CPV Modules
- Tracker
- O Tracker Control Unit
- O Air Drying Unit

A specific cabling and tubing set completes the CPV System.

Soltec's system integration process ensures that the components fully work together and the CPV System operates safely and reaches its full performance. The CPV System can only be operated with the components described in this document.

The CX-SS30-II CPV System comes in different variants. For example there are USand Rest-of-World variants of the Tracker Control Unit or integrated or centralized variants of the Air Drying Unit.

The following chapters describe the variants of the CPV System main components and provide a guideline on how to select the correct component for a particular power plant project.

Contact Soitec for component availability and questions regarding component selection.





Fig. 2-2 CPV System CX-5530-II, rear view (left), side view (right)

© Soitec | CK-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29

CO - Public

Page 4

#### CX-M500 CPV Module Description 2.1

Description One CPV System includes 12 CPV Modules.

A CPV Module consists of solar cell assemblies (SCAs) on the glass receiver plate, and Fresnel lenses on the top lens plate, surrounded by a metal frame. Within one CPV System, DC cables are used to interconnect the CPV Modules. The CPV Module is hollow inside and has an air tube connection point at one end and a membrane permeable to air at the other. A profile rail exists on each side and also in the middle underneath the CPV Module. The profile rail is used for the attachment of the module

Function CPV Modules generate and output DC power during the day.

Two variants of the CX-M500 CPV Module exist.

CX-M500 with junction box DC connectors (IEC certified).

CX-M500 with pigtail DC connectors (IEC and UL certified).

For CPV System installations in the US, CX-MS00 with pigtall DC connectors will preferably be used. Usage of CX-M500 with junction box DC connectors in the US is also possible, it requires however a field certification. For CPV System installations outside the US, both CX-M500 with junction box and pigtail DC connectors can be used.

Aside from the DC connectors and module certifications, the two CX-M500 variants are identical, they share the same mechanical and electrical technical data. In the long term, Soltec will only provide CX-MS00 with pigtail DC connectors. Contact Soltec for component availability and questions regarding component selec-




Fig. 2-3 CX-M500 CPV Module and DC connectors. Junction box (above) pigtall (below)

Page 5

CO-Public

CX-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 (i) Soitec

October 2015 7345

# 2.2 CX-T030-II Tracker Description

**Description**The Tracker is a mechanical steel structure consisting of a mast, a drive with azimuth and elevation motors, ribs, stringers, and brackets to secure the CPV Modules.

Function The Tracker performs the following functions:

- Supports the CPV Modules.
- O Moves to follow the sun during the day.

The CX-T030\_II Tracker exists in two different variants. Both share the same design.

CX-T030-II\_US with minor US-specific adaptations of the design addresses the requirements of CPV power plants built in the US.

CX-T030-II\_RoW serves power plant installations outside the US.

With both Tracker variants, the full CPV System safety and performance is achieved. Contact Soltec for component availability and questions regarding component selection.



Fig. 2-4 CX-T030-II\_US



Fig. 2-5 CX-T030-II\_RoW

© Soitec | CX-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29

CO - Public

Page 6

# 2.3 CX-TC2 Tracker Control Unit Description

Description The Tracker Control Unit controls the Tracker movements to enable the CPV System to follow the sun throughout the day. It is also used to monitor and control the CPV

> The Tracker Control Unit is controlled via the SCADA system from any location within or outside the CPV Power Plant, using communication interfaces.

Function The Tracker Control Unit performs the following functions:

- O Operates the Tracker movement.
- Directs the AC power supply to the motors and other components of the CPV
- Measures the DC power output of the CPV System.
- Communicates with the Meteo Analyzer Unit and SCADA System.

The CX-TC2 Tracker Control Unit exists in two different variants.

CX-TC2\_US addresses the requirements for CPV power plants built in the US.

CX-TC2\_RoW serves power plant installations outside the US.

With both Tracker Control Unit variants, the full CPV System safety and performance

Contact Soltec for component availability and questions regarding component selec-





Fig. 2-6 Tracker Control Unit CX-TC2\_RoW (left), CX-TC2\_US (right)

Page 7

CO-Public

CX-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 (c) Soitec

October 2015 7345

#### 2.4 CX-AD1 and CX-AD2 Air Drying Unit Description

Description The Air Drying Unit primarily consists of a blower and drier to provide dried air to CPV Modules. A set of tubing goes from the Air Drying Unit to each of the CPV Mod-

Function The Air Drying Unit blows dry air into the CPV Modules to ensure a low relative humidity of air inside the CPV Modules.

There are two different Air Drying Units for the CPV System CX-S530-II.

CX-AD1 reflects an integrated design approach where the Air Drying Unit is installed within the CPV System. It is possible to use one CX-AD1 in one CPV System. Alternatively one CX-AD1 can be shared between a maximum of three CX-S530-II CPV Systems. This approach provides advantages for smaller power plants.

CX-AD2 is foreseen for centralized usage in a power plant where CX-AD2 is installed independently from the CPV Systems. One CX-AD2 can serve multiple CX-S530-II CPV Systems.

For CX-AD1 a CE conformity declaration has been issued by Soitec. For CX-AD2 CE conformity will be declared and it will be also UL listed.

For CPV System installations in the US, the UL listing of CX-AD2 provides an advantage. Usage of CX-AD1 in the US is also possible, requires however a field certification. With both Air Drying Units, the full CPV System safety and performance is achieved.

Contact Soitec for component availability and questions regarding component selection.



Fig. 2-7 Air Drying Unit CX-AD1 (left), CX-AD2 (right)

© Soitec | CX-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29

CO - Public

Page 8

October 2015

# 3 CX-5530-II CPV System Technical Data

# 3 CX-S530-II CPV System Technical Data

Туре	CX-S530-II
Number / type of CPV Modules	12 CPV Modules / CX-M500
Certifications, compliance, listings	CE
Aperture area	94 m <sup>2</sup> / 1010 sq ft
Module area	105 m <sup>2</sup> / 1130 sq ft
Array area	110 m <sup>2</sup> / 1180 sq ft
Ground coverage ratio (at horizontal po- sition)	16% with 27 m x 25 m / 89 ft x 82 ft spacing of CPV Systems (Spacing may differ for particular power plant projects)
Maximum height (at steep; horizontal position)	8.0 m / 26 ft; 4.8 m / 16 ft
Data valid under nominal conditions: DN	I=1000 W/m <sup>2</sup> , AM1.SD, T <sub>cell</sub> =25°C
DC power at MPP (P <sub>MPP</sub> )	29.4 kW <sub>p</sub> ± 10% <sup>(1)</sup> (sum of CPV Modules power)
Data valid under operating conditions: D	NI=900 W/m <sup>2</sup> , AM1.5D, T <sub>amb</sub> =20°C, Wind speed=2m/s
DC power at MPP (P <sub>MPP</sub> )	24.2 kW ± 10% (1)
DC voltage at MPP (V <sub>MPP</sub> )	600 V (1)
DC current at MPP (I <sub>MPP</sub> )	40 A (1)
DC open-circuit voltage (V <sub>OC</sub> )	690 V (1)
DC short-circuit current (I <sub>SC</sub> )	46 A (1)
DC efficiency (aperture)	28.6% (1)

(1) Indicative values




Fig. 3-8 CX-SS30-II CPV System dimensions, front view horizontal position (left), side view steep position (right)

Page 9 CO-Public CX-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_vS2\_EN\_2014-01-29 (c) Soites

#### 4 CX-M500 CPV Module Technical Data 4 CX-M500 CPV Module Technical Data CX-M500 Type DC connectors type Pigtail Junction box Concentrator type Point focusing silicone on glass Fresnel lenses Concentration ratio CE, UL 62108, UL SU 8703, IEC Certifications, compliances, list-CE, IEC 62108, IEC 62688 draft, CEC listing 62108, IEC 62688, CEC listing Dimensions (L x W x H) 3.67 m x 2.39 m x 0.102 m / 12.0 ft x 7.84 ft x 0.335 ft Weight 210 kg / 460 lbs 2400 Triple junction cells per CPV Module Solar Cell quantity and type Solar Cell cooling system Passive cooling with metal heat sink Solar Cell max. temperature 55 K above ambient temperature Operating ambient temperature -20°C to +55°C / -4°F to +130°F 0.06%/K at T<sub>amb</sub><21°C/70°F (1); -0.34%/K at T<sub>amb</sub>≥21°C/70°F (1) Temp. coefficient (P<sub>MMP</sub>) -0.14%/K (1) Temperature coefficient (V<sub>OC</sub>) 0.20%/K at T<sub>amb</sub><21°C/70°F (1); -0.20%/K at T<sub>amb</sub>≥21°C/70°F (1) Temperature coefficient (I<sub>SC</sub>) Temperature coefficient graph (Graph does not include tolerances) -4% Data valid under CSTC acc. to IEC 62670-1: DNI=1000 W/m2, AM1.5D, Tcell=25°C DC power at MPP (PMPP) 2450 Wp ± 10% (1) DC voltage at MPP (V<sub>MPP</sub>) 645 V (1) 3.8 A (1) DC current at MPP (I<sub>MPP</sub>) DC open-circuit voltage (V<sub>OC</sub>) 740 V (1) 4.2 A (1) DC short-circuit current (I<sub>SC</sub>) 31.8% (1) DC efficiency (aperture) Data valid under CSOC acc. to EIC 62670-1: DNI=900 W/m<sup>2</sup>, AM1.5D T<sub>ambient</sub>=20°C, Wind speed=2m/s DC power at MPP (PMPP) 2040 W ± 10% (1) 600 V (1) DC voltage at MPP (V<sub>MPP</sub>) 3.4 A (1) DC current at MPP (I<sub>MPP</sub>) 690 V (1) DC open-circuit voltage (Voc) DC short-circuit current (I<sub>SC</sub>) 3.8 A (1) DC efficiency (aperture) 29.0% (1) (1) indicative values © Soitec | CX-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 CO - Public Page 10

#### 5 CX-T030-II Tracker Technical Data

## 5 CX-T030-II Tracker Technical Data

Туре	CX-TC	30-II
Extended type number	CX-T030-II_RoW	CX-T030-II_US
Tracking type	Two-axis tracking,	rotational elevation
Certifications, compliances, listings	CE	(in progress: UL)
Motors type		; suited for / 50Hz or 60Hz
Elevation movement range	5° to	90° (1)
Azimuth movement range	30	0.0
Motor protection class	IP	55
Power consumption typ. / max.	110VA / 810VA respectively 100W / 800W	90VA / 680VA respectively 85W / 670W
Max. tracking wind speed		31 mph to 40 mph pon project site)
Max, survival wind speed	40 m/s /	90 mph
Weight Tracker table including drive (without CPV Modules and cabling)	2500 kg / 5500 lbs	2600 kg / 5700 lbs
Weight mast	460 kg / 1000 lbs (for a 3.6 m/12 ft flange mast) (2)	470 kg / 1000 lbs (for a 3.6 m/12 ft flange mast) (2)
Operating ambient temperature	-20°C to +55°C	/ -4°F to +130°F

- 5° Tracker table steep position 90° Tracker table flat position
- (2) mast type and length depends on project soil conditions and foundation.

Page 11 C0-Public CV-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 (i) Soltec

6 CX-TC2 Tracker Control Unit Technical Data

## 6 CX-TC2 Tracker Control Unit Technical Data

Туре	cx-	CX-TC2	
Extended type number	CX-TC2_RoW	CX-TC2_US	
Certifications, compliances, listings	CE	(in progress: UL 3703, UL 508A)	
Tracking modes	Maximum Power Point, A	stro- and Sensor-tracking	
Tracker motors drive	AC 3	phase	
Communication interface	Ethe	ernet	
Protection class (if all cables connect- ed and cable glands closed)	IP 65	NEMA 4	
Electrical connection (supply)	1-phase; 230V ± 10%, 50 Hz	208V phase-phase or 230V phase-neutral ± 10%; 60 Hz	
Power consumption typ-/max. (without motors consumption)	70 VA / 80 VA respectively 20 W / 25 W	70 VA / 80 VA respectively 20 W / 25 W <sup>(1)</sup>	
Max. DC input voltage	800V	1000V	
Max. DC input current	66	D A	
DC measurement accuracy	±	2%	
Dimensions (L x W x H)	210 mm x 760 mm x 760 mm / 0.69 ft x 2.5 ft x 2.5 ft	200 mm x 760 mm x 760 mm / 0.67 x 2.5 ft x 2.5 ft	
Weight	50 kg / 110 lbs	58 kg / 130 lbs	
Operating ambient temperature	-20°C to +55°C	/ -4°F to +130°F	

<sup>(1)</sup> indicative values

© Soltec | CX-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29

CO - Public

Page 12

7 CX-AD1 Air Drying Unit Technical Data

# 7 CX-AD1 Air Drying Unit Technical Data

Туре	CX-AD1	
System architecture	One CX-AD1 per CX-SS30-II or One CX-AD1 shared between max. 3 CX-SS30-II	
Integration	Fully integrated, single unit design	
Certifications, compliances, listings	Œ	
Communication interface	RS232	
Number of air outlets	4	
Protection class	IP 03	
Electrical connection (supply)	1-phase, 208 V or 230 V ± 10%; 50 Hz or 60 Hz	
Power consumption idle typ./max.	9 VA / 11 VA respectively 3 W / 5 W	
Power consumption drying typ./max.	140 VA / 190 VA respectively 100 W / 140 W	
Power consumption regeneration typ./max.	380 VA / 560 VA respectively 250 W / 380 W	
Dimensions (L x W x H)	289 mm x 545 mm x 974 mm / 0.95 ft x 1.79 ft x 3.20 ft	
Weight	15 kg / 33 lbs	
Noise emission idle	Noiseless (not measurable)	
Noise emission drying and regeneration	75 dB(A) (sound power level)	
Operating ambient temperature idle and regeneration	-20°C to +50°C / -4°F to +122°F	
Operating ambient temperature drying	-20°C to +30°C / -4°F to +86°F	

Page 13 CO-Public CV-SS30-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29 (C) Soitec

8 CX-AD2 Air Drying Unit Technical Data

# 8 CX-AD2 Air Drying Unit Technical Data

Туре	CX-AD2 (1)	
System architecture	One CX-AD2 shared between max. 56 CX-S530-II	
Integration	Centralized, compressor and pneumatic box	
Certifications, compliances, listings	CE (in progress: UL 60335-2-40, UL 474, UL 60730-2-13A)	
Communication Interface/Protocol	Ethernet/Modbus via TCP/IP (at pneumatic box)	
Number of air outlets	14, each for max. 4 CX-S530-II	
Air tubing connectors	Metric	
Protection class	IP 55, operation under shelter	
Electrical connection (supply)	1-phase, 208 V or 230 V ± 10%; 50 Hz or 60 Hz	
Power consumption idle typ.	120 VA respectively 95 W	
Power consumption drying typ.	5500 VA respectively 4100 W	
Dimensions (L x W x H)	1.58 m x 0.84 m x 1.30 m / 5.18 ft x 2.76 ft x 4.27 ft	
Weight	230 kg / 510 lbs	
Noise emission idle	Noiseless (not measurable)	
Noise emission drying	1 m 71 dB (A), 25 m 43 dB(A)	
Operating ambient temperature idle	-20°C to + 55°C / -4°F to + 130°F	
Operation ambient temperature drying	-20°C to + 30°C / -4°F to + 86°F	

(1) for availability contact Soitec

© Soitec | CX-5530-II\_29.4kWp\_Technical\_Data\_Sheet\_v52\_EN\_2014-01-29


CO - Public

Page 14

October 2015

7345

O9 40








# The most efficient solar generator for clean, off-grid electricity

Soitec Plug&Sun uses field-proven Concentrix technology. The complete system (3 trackers) delivers up to 3.4 kW<sub>ii</sub> and dual-axis tracking technology ensures constant energy production throughout the day. Coupled to batteries, the system provides electricity 24/7. Designed for easy deployment, Plug&Sun is compliant with local electricity standards to easily connect electrical devices.





October 2015



#### Hingtgen, Robert J

Sent: To: Donna Tisdale <tisdale.donna@gmail.com>

Sunday, March 02, 2014 12:35 PM

Hingtgen, Robert J. Fogg, Mindy, Gungle, Ashley, Jacob, Dianne; Wilson, Adam; Kohatsu, Sachiko; Sprecco, Edward; Gutierrez, Gabriel; Cox, Greg

Sachiko: Sprecco, Edward; Gutierrez, Gabriel; Cox, Greg Soitec Solar falls to disclose truth

Subject:

Berkman Soitec CEQA-NOW to SBC 2-28-14 pdf

#### FOR SOITEC SOLAR DPEIR RECORD

Hello Robert,

If you have not already done so, please include the following documents into the record:

 The March 1st East County Magazine article on Soitec Solar and their controversial Newberry Solar 1 site. The article is pasted below and posted online at: <a href="http://eastgountymagazine.org/print/15060">http://eastgountymagazine.org/print/15060</a>

The attached letter from the Newberry Springs group CEQA-NOW, signed by Robert Berkman and dated 2-28-14. It raises non-compliance issues with Soitec's controversial 1.5 MW project in their neighborhood, which triggered the temporary San Bernardino solar moratorium.

Thank you,

Donna Tisdale 619-766-4170

SOITEC FAILS TO DISCLOSE TRUTH ABOUT SOLAR PROJECT IMPACTS, HIRES EX- SAN DIEGO COUNTY PLANNING OFFICIAL WHO OVERSAW SOITEC PROJECTS 09-4

09-4


The East County Magazine article dated March 1 and attached to the comment letter is noted. Comments regarding the moratorium on solar projects in San Bernardino County do not concern or relate to the adequacy of the analysis included in the DPEIR and as such, no response is required. However, it should be noted that the DPEIR analyzes potential impacts associated with new sources of project-generated glare and concludes that despite the implementation of mitigation and project design features, glare impacts would be significant and unmitigable (see DEPIR Section 2.1.3.3, Light and Glare). Comments regarding claims made in brochures produced by Soitec also do not concern the adequacy of the environmental analysis included in the PEIR but it should be noted that the FPEIR discloses the anticipated cut and fill quantities associated with development of the Tierra del Sol and Rugged solar farm sites (see FPEIR page 1.0-13). In addition, the anticipated construction and operational water demands associated with the Proposed Project are described in Chapter 1.0, Project Description of the FPEIR and potential impacts to biological resources are described in Chapter 2.3, Biological Resources. The referenced fact sheets are noted but do not concern the adequacy of the environmental analysis included in the DPEIR and therefore, no additional response is required or provided. Please refer to responses to comments C2-68 and I106-1 regarding

October 2015

7345

Final PEIR

# **Response to Comments**



Patrick Brown's employment with Soitec. Please refer to common response WR1 regarding construction and operational water demand estimates included in the DPEIR and necessary revisions made in the FPEIR.

Why doesn't San Diego County end revolving door/conflict of interest situation?

October 2015 7345

Final PEIR

Photo: Soitec's Newberry Springs project, which promised minimal enviornmental impacts, graded all vegetation on the site.

By Miriam Raftery

March 1, 2014 (San Diego's East County)—Developers frequently put "spin" on project descriptions to emphasize benefits rather than negative impacts. But certain statements by Soitice representatives regarding its proposed solar projects in Boulevard and a recent project in the desert fall into the "Pinnochio." In fact Soitice representatives misrepresented glure issues and the amount of land that is disturbed by their projects.

During a Soitee community meeting at the Manzanita Diner last month, ECM's editor asked Soitee media and communications advisor Karen Hutchens specifically about a moratorium on solar projects approved by San Bernadino County Supervisors amid concerns about glare in Newberry Springs, where Soitee built a project very similar to its proposed Boulevard sites. Hutchens responded, "That had nothing to do with our project. The moratorium was passed before our project was even built."

But Robert Berkman, head of a citizens group in Newberry Springs called CEQA-NOW, told ECM that statement was a baid-faced lie. "The moratorium came out because of the Soitee project—after it was built," he said, adding that citizens invited Supervisors to visit the site. Supervisors said, ""Good grief, what has happened here? "Berkman stated. "The moratorium occurred because we were able to bring them out and say This is an example of solar done wrong."

That's not the only whopper Soitec has told.



Deceptions on grading sites, protecting plants and

At Boulevard's planning group meeting and in other discussions with the public and press, Soitec has repeatedly promised it would make efforts to minimize environmental impacts and has stated that it would not scrape bare vast tracts for its projects. The company brochurg makes similar claims including "no grading of water required" and "minimal impact on vegetation and wildlife."

But the Newberry Springs project, which has the same sized Soitee solar modules proposed for Boulevard, proves otherwise, as numerous photos sent by CEQA-NOW shows. (photos, top left and right, for example).

"These claims are demonstrated as false when based on their estimated grading and water use and other significant impacts for Rugged Solar, Tierra Del Sol Solar, LanWest and LanEast, removal of agriculture preserve, and through other information included in the DPEIR, and as demonstrated by Soitec's other projects," Boulevard Planning Group Chair Douna Tisdale says of Soitec's claims regarding no grading and minimal

O9-4 Cont.

October 2015 7345

wildlife

environmental impacts at its Boulevard sites. "The false claims, regarding no grading and minimal impact on vegetation and wildlife, are also contradicted by Soitec's own public relations Fact Sheets, and other documents, with evidence of clear grading, removal of virtually all vegetation, and disturbance of natural soil / binders at their following existing sites," she added.

- Soitec's 1.37MW Questa New Mexico facility Fact Sheet (173 Concentrix 18'x 21' CPV dual trackers): claims of zero water gallons per year for power production http://www.soitec.com/pdf/sites/Soitec\_Questa\_factsheet\_en.pdf
- Soitee's 1.68 MW Newberry Solar 1 site in Newberry Springs, CA (60 CX-S530 CPV systems)
   Newberry Springs ID Card: <a href="http://www.soitec.com/pdf/sites/Soitec\_Newberry\_ID\_card.pdf">http://www.soitec.com/pdf/sites/Soitec\_Newberry\_ID\_card.pdf</a>
- Soitee's Newberry Springs PR video (see video starting at 2:31 minutes for evidence of clear grading at Newberry site and at 3:30 where the video fades out just as the main glare from the CPV punels would show up/http://www.soitec.com/videos/soitec-newberry-springs/
- Soitee's Hazelemer 500kV site Durban South Africa Fact Sheet (32 CX-S42 systems): http://www.soitee.com/pdf/sites/Soitee\_Hazelmere\_factsheet\_en.pdf
- Soitee's Wadi El Natrun Egypt 40kW Fact Sheet (5 Soitec CX-P6 systems) http://www.soitec.com/pdf/sites/Soitec Wadi El Natrun factsheet en.pdf
- Soitec's Touwsrivier Western Cape South Africa 82kW (demonstration project) Fact Sheet (Soitec CX-P6): http://www.soitec.com/pdf/sites/Soitec Touwsrivier\_factsheet\_en.pdf
- Soitec's 680kW Puertollano, Castilla-La Mancha, Spain CPV plant Fact Sheet (Soitec CX-P6): http://www.soitec.com/pdf/sites/Soitec Puertollano foctsheet en.pdf
- Soitec's 630kW Rains, Var., France Fact Sheet (80 32m2 CPV Systems): http://www.soitec.com/pdf/sites/Soitec\_Rians\_factsheet\_en.pdf

These and other projects are documented in the Soitee CPV Installation document dated. February 2014, where all but 2 of the 12 projects shown are clear graded: http://www.suitee.com/pdf/Soitee\_CPV\_Installations\_V10.0.pdf

Newberry Springs residences complain of major changes not disclosed, mitigation not enforced

Softee pulled a bait-and-switch tactic in Newberry Springs after acquiring the project site from another company that had proposed panels only about serven feet tall. The company assured community members that environmental impacts would be minimal. Residents report they were shocked to see the entire site bladed, every piece of vegetation removed along with the crust of desert soil, and modules 27 feet high erected which blocked views of the Newberry Mountains Wilderness area.

Those facts are detailed in a letter sent February 28, 2014 by CEAQ-NOW to Tom Hudson, director of San Bernadino County's Land Use Services Department. The letter further alleges that many if not all proposed mitigations "have somehow disappeared" including a living fence to screen visual impacts, soil stabilization to reduce blowing sand, and road improvements.

Shockingly, the lotter further asserts that Soiteo's permitting manager, Patrick Brown, stated that the company had not retained records including signed applications for any amended conditions of approval, nor signed approvals for amended conditions of approval – such as the massive change in height.

Soitec's plans for a phase II of its project have been stalled, though the moratorium on new solar projects was later lifted.

O9-4 Cont.

### County planner who reviewed Soitee projects here takes job with Soitee



Diego County residents, it's because Brown was the San Diego County Department of Planning and Development's Project Manager assigned to review Soitec's solar applications pending locally before switching jobs to work for Soitec – a move Berkman observes wryly was 'not a confidence builder from our point."

This is far from the first time that San Diego County has faced criticism over its revolving door policies. Other official bodies such as Congress impose moratoriums or a year or more before a county official can go to work for a company they oversaw, or vice versa. Back in 2006, this writer exposed in a story published at RawStory that a former Blackwater attorney, Lori Spar, went to work soon after leaving the firm to become an environmental planner with the County overseeing the Blackwater paramilitary training camp project proposed in Potero. That report won a prize from San Diego Press Club. The County confirmed that it has no time limits to prevent such revolving door situations, creating fertile grounds for conflicts of interests.

O9-4 Cont.

#### Concerns over Soitec consultants' water estimates



This is also not the first time that serious concerns have been raised over Soitec estimates of its projects' impacts. As ECM has previously reported, the company's environmental consulting firm, Dudek, has a troubled track record of severely underestimating water usage at various projects, notably the Eco-Substation in Boulevard that used three times more water than Dudek estimated, as ECM has reported.

\$

Local planners have exposed that Dudek's estimated water use in the Soitee solar draft Environmental Impact Report for its four proposed Boulevard industrial solar projects (including site shown in photo, right) omitted concrete making operations and rock-crushing planned onsite, both very water intensive uses, among other items omitted.

An SDSU hydrologist has said even the levels Soitec estimates could destroy the region's ecosystem, draining groundwater resources beyond the level that can be replenished, a joint investigation by ECM and Eco Report revealed. Cleveland National Forest Foundation and Anza Borrego Foundation have joined the fight against Soitee's projects, citing irreversible harm the projects could pose to the national forest and California's largest state park.

#### Who is Soitec?

Soitec opened a solar manafacturing facility in San Diego in Docember 2012 after receiving a \$25 million grant from the U. S. Department of Energy to develop its mamfacturing base here. The French-based company known for developing its flagship material, \$01 (Silicon-on-Insulator,) Jean-Michel Lamure and André-Jacques Auberton-Hervé founded the company in 1992, collaborating on developing and commercializing their Smart Cut<sup>TM</sup> "atomic scalpel" technology. Soitee focuses on five industries: computing, telecommunications, automotive electronics, lighting, and solar energy.

Initially, Soitec's main focus was in the electronics industry. However, several years ago, Soitec launched into the solar energy industry. Currently, the company owns solar and wind energy facilities in France, the United States, Germany, Italy, Asia, China, Korea, Jagun, Singapore, and Taiwan.

In 2011, Soitec Solar Development, LLC, received the approval of five of its power purchase agreements with San Diego Gas and Electric (SDG&E) from the California Public Utilities Commission (CPUC). These five projects represent a combined capacity of 155megawatts (MW) of solar energy with electricity generated at solar power plant sites in San Diego County.

#### Lessons from a troubled track record

While Supervisors have been supportive of Soitee efforts to create manufacturing jobs locally, the company's efforts to deceive planners, public officials and residents about the real impacts of its first proposed projects in San Diego's East County—and in Newberry Springs—should give decision makers pause to examine the veracity of all claims made by Soitee.

Voters should also question why County officials have not yet seen fit to end the County's revolving door policy that allows planning officials to profit off decisions by accepting lucrative offers from the very developers they are supposed to monitor to protect the public's interests and conversely, allow corporate proponents to take jobs overseeing the very projects they were formerly advocating for with the County. Such cozy arrangements enable potential corruption, though it's not clear what incentives if any Soitee may have offered Brown to push forward its projects while working with the County before he became a paid company advocate.

## Public comment period ends March 3 for Soitec proposed solar projects in Boulevard

Public comments on the project are being accepted through March 3<sup>rd</sup>. For details on how to submit comments, see <a href="http://www.eastcountymagazine.org/node/14938">http://www.eastcountymagazine.org/node/14938</a>.

O9-4 Cont.

INTENTIONALLY LEFT BLANK

October 2015 Final PEIR 7345